



### **SUPERVISOR'S DECLARATION**

I hereby declare that I have checked this thesis and in my opinion, this thesis is adequate in terms of scope and quality for the award of the degree of Bachelor of Engineering in Mechatronics.

A handwritten signature in black ink, appearing to read 'Dr. Muhammad Azzat Bin Zakaria', is written over a horizontal line.

(Supervisor's Signature)

Name of supervisor : DR. MUHAMMAD AIZZAT BIN ZAKARIA

Position : SENIOR LECTURER

Date : 3<sup>RD</sup> MARCH 2017



## STUDENT'S DECLARATION

I hereby declare that the work in this thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at Universiti Malaysia Pahang or any other institutions.

A handwritten signature in black ink, appearing to read 'Izzad', is written above a horizontal line.

(Student's Signature)

Full Name : MOHAMMAD IZZAD BIN MOHAMMAD  
IDZLALUDDIN

ID Number : HA12016

Date : 3<sup>RD</sup> MARCH 2017

# THREAT ASSESSMENT ANALYSIS FOR VEHICLE COLLISION AVOIDANCE

MOHAMMAD IZZAD BIN MOHAMMAD IDZLALUDDIN

Thesis submitted in fulfillment of the requirements  
for the award of the degree of  
Bachelor of Engineering in Mechatronics Engineering

Faculty of Manufacturing Engineering  
UNIVERSITI MALAYSIA PAHANG

MARCH 2017

PERPUSTAKAAN 271017 UNIVERSITI MALAYSIA PAHANG P	
No. Perolehan <b>119959</b>	No. Panggilan EKP -199 2017 v Bc.
Tarikh <b>12 OCT 2017</b>	

## **ACKNOWLEDGEMENTS**

First and foremost, I am grateful to Allah, the Almighty God for giving me strength and motivation to complete my research studies within this short period of time.

I wish to express my deepest gratitude to my supervisor in University Malaysia Pahang, Dr. Muhammad Aizzat Bin Zakaria for giving me the opportunity to conduct this research under his supervision. He always encourages me to do the best and help me get through this project. Although he is busy with his works and lectures, he still manages to spend time to help me. I am proud to have him as my Final Year Project's supervisor.

I place on my record, my sincere gratitude to my supervisor from Hochschule Karlsruhe – Technik und Wirtschaft (HsKA), Germany, Prof. Helmut Scherf for guiding me and giving his opinions about this project during all the Skype presentation sessions.

I would also like to thank one and all who, directly or indirectly, have lent their helping hand in this venture. This includes, a lecturer from Faculty of Mechanical Engineering, Dr. Mohamad Heerwan bin Peeie and my fellow course mates.

Last but not least, I wish to express my deepest appreciation to my loving parents and family for their never ending support and prayers throughout my degree journey.



## **ABSTRACT**

This thesis presents a threat assessment analysis for collision avoidance just before an accident. This is due to the high rate of accidents that happened in Malaysia for the past years. The outcome of this research is to simulate the vehicle's maneuver trajectory to prevent accidents. Besides that, possible impacts of the accidents will be estimated for threat assessment analysis. This project also provides an appropriate decision making for the driver by assessing different vehicle's maneuver conditions. There are different cases of avoidance such as the driver of a vehicle can use braking, acceleration or steering to avoid a collision with an obstacle model. An intelligent threat analysis is proposed to estimate the possible position of the main vehicle to generate a minimum impact force of potential accidents. The analysis proposed will help the driver to make decision to avoid an obstacle. In addition, the environment uses MATLAB/Simulink for simulation to estimate the position. The simulation includes system blocks of vehicle dynamics, kinematics of a car and obstacle modelling. Simulation results and theoretical value of impact forces are able to determine the suitable position of vehicle to avoid obstacles.

## ABSTRAK

Projek ini menerangkan tentang penilaian ancaman analisis bagi mengelakkan perlanggaran antara kenderaan. Projek ini dilaksanakan oleh kerana kadar kemalangan yang tinggi di Malaysia sejak beberapa tahun yang lalu. Dapatan kajian yang dilakukan ini adalah bagi mensimulasikan trajektori kenderaan bagi mengelakkan perlanggaran. Selain itu, impak perlanggaran akan dinilai bagi tujuan penilaian ancaman analisis. Projek ini juga membantu dalam memberi keputusan yang sesuai untuk pemandu dengan menilai cara mengelak perlanggaran. Terdapat pelbagai cara untuk mengelakkan perlanggaran sesama kenderaan. Antaranya ialah pemandu boleh menekan brek, menekan pedal minyak atau memusing stereng kereta bagi mengelakkan perlanggaran. Penilaian ancaman analisis telah diusulkan untuk membuat keputusan dan anggaran tentang kedudukan kereta bagi mengelak perlanggaran atau membuat perlanggaran dengan minima impak terhadap pemandu. Tambahan pula, perisian Matlab/Simulink akan digunakan sebagai perisian simulasi bagi menentukan kedudukan kereta tersebut. Simulasi yang akan dilakukan termasuklah kenderaan model dinamik, model kinematik dan model halangan. Hasil keputusan simulasi dan nilai teori daya impak dapat menentukan kedudukan kenderaan yang sesuai bagi mengelakkan halangan.

## TABLE OF CONTENT

SUPERVISOR'S DECLARATION	
STUDENT'S DECLARATION	
ACKNOWLEDGEMENT	ii
ABSTRACT	iii
ABSTRAK	iv
TABLE OF CONTENTS	v
LIST OF TABLES	vii
LIST OF FIGURES	viii
LIST OF SYMBOLS	x
LIST OF ABBREVIATIONS	xii

### CHAPTER 1 INTRODUCTION

1.1	Background of Project	1
1.2	Problem statement	2
1.3	Project objectives	2
1.4	Project scope	3

### CHAPTER 2 LITERATURE REVIEW

2.1	Study of impacts	4
2.2	Study of collisions	6
2.3	Study of vehicle dynamics	
2.3.1	Vehicle model	8
2.3.2	Longitudinal force and Lateral force	11
2.3.3	Kinematics model	15
2.3.4	Driver model	16
2.3.5	Braking distance	17
2.4	Threat assessment analysis	18
2.5	Study of multiple vehicles' maneuver condition	19
2.6	Literature review gap	22
2.7	Summary	22



## CHAPTER 3 METHODOLOGY

3.1	Introduction	23
3.2	Flowchart	24
3.3	Mathematical modeling	
3.3.1	Vehicle dynamics model	25
3.3.2	Kinematics model	28
3.3.3	Obstacles model	29
3.3.4	Threat assessment analysis	29
3.4	Multiple vehicles' maneuver conditions	30
3.5	Model design	
3.5.1	Overall Simulink model design	32
3.5.2	Simulink model design	33

## CHAPTER 4 RESULTS AND DISCUSSION

4.1	Introduction	38
4.2	Table of input and output parameters for all cases	39
4.3	Theoretical calculation	
4.3.1	Case 1: Braking	40
4.3.2	Case 2: Hitting obstacle directly	41
4.3.3	Case 3: Steers to the right	43
4.3.4	Case 4: Steers to the left	45
4.3.5	Special case study	47
4.4	Simulation result	
4.4.1	Case 2: Hitting obstacle directly	48
4.4.2	Case 3: Steers to the right	49
4.4.3	Case 4: Steers to the left	50
4.3	Discussion	52

## CHAPTER 5 CONCLUSION

5.1	Introduction	54
5.2	Conclusion	55
5.3	Recommendations	56

REFERENCES	57
------------	----

APPENDIX A	59
------------	----

## LIST OF TABLES

Table 2.1	Equations of momentum and kinetic energy	8
Table 3.1	Symbols used in Vehicle dynamics model	27
Table 3.2	Symbols used in kinematics model	29
Table 3.3	Input parameters	31
Table 3.4	Output parameters	31
Table 3.5	Example of tabulation of data for the calculation of force impact	31
Table 4.1	Parameters involved for all cases	39
Table 4.2	Parameters used in case 2	42
Table 4.3	Parameters used in case 3	44
Table 4.4	Parameters used in case 4	46
Table 4.5	Comparison between all cases when velocity is constant	47
Table 4.6	Comparison between case 1, case 2, case 3 and case 4	52



## LIST OF FIGURES

Figure 1.1	General Road Accident Data in Malaysia (1997 – 2014) – Malaysian Institute of Road Safety Research (MIROS)	2
Figure 2.1	Calculation of force on Car	5
Figure 2.2	How to minimize impact force	6
Figure 2.3	Example of inelastic collision	7
Figure 2.4	The illustration of vehicle model	8
Figure 2.5	Equations used for vehicle model	9
Figure 2.6	The illustration of bicycle model	10
Figure 2.7	Example of tire model and vehicle model	10
Figure 2.8	Pacejka '94 Longitudinal Force parameters	12
Figure 2.9	Pacejka '94 Lateral Force parameters	14
Figure 2.10	Vehicle's position	15
Figure 2.11	Vehicle model in local and global coordinates	16
Figure 2.12	Example of driver model	17
Figure 2.13	Example of braking calculation	17
Figure 2.14	Possible vehicles' evasive maneuver	19
Figure 2.15	Investigated cases by crash type, 2008	20
Figure 2.16	Investigated cases on curve or straight road, 2007–2010	20
Figure 2.17	The frequency distribution of the movement prior to critical crash	21
Figure 3.1	Flowchart of threat assessment for vehicle collision avoidance	24
Figure 3.2	Vehicle dynamics model	25
Figure 3.3	Kinematics model of a vehicle in a lane	28
Figure 3.4	Different vehicles' maneuver conditions	30

Figure 3.5	Overall Simulink model design	32
Figure 3.6	Simulink model for equation (3)	33
Figure 3.7	Simulink model for equation (4)	34
Figure 3.8	Simulink model for equation (1) and (2)	35
Figure 3.9	Simulink model for equation (5)	36
Figure 3.10	Simulink model for equation (6) and (7)	37
Figure 4.1	Calculation to find braking distance	40
Figure 4.2	Vehicle hits a static object	41
Figure 4.3	Head-on collision between two vehicles	43
Figure 4.4	Vehicle hits environmental object	45
Figure 4.5	Simulation for case 2	48
Figure 4.6	Simulation for case 3	49
Figure 4.7	Simulation for case 4	50

## LIST OF SYMBOLS

$F$	Force
$m$	Mass
$a$	Acceleration
$d$	Distance
$t$	Time
$\dot{V}_x$	Longitudinal acceleration
$\dot{V}_y$	Lateral acceleration
$V_x$	Longitudinal velocity
$V_y$	Lateral velocity
$F_{x\text{ fr}}, F_{y\text{ fr}}$	Forces of $F_x$ and $F_y$ at front right wheel
$F_{x\text{ fl}}, F_{y\text{ fl}}$	Forces of $F_x$ and $F_y$ at front left wheel
$F_{x\text{ rr}}, F_{y\text{ rr}}$	Forces of $F_x$ and $F_y$ at rear right wheel
$F_{x\text{ rl}}, F_{y\text{ rl}}$	Forces of $F_x$ and $F_y$ at rear left wheel
$\delta$	Steering angle
$m$	Mass of vehicle
$\ddot{r}$	Yaw motion
$\dot{r}$	Yaw rate
$w$	Vehicle track width
$L_f$	Length from vehicle COG to front wheels
$L_r$	Length from vehicle COG to rear wheels
$V$	Longitudinal velocities
$U$	Lateral velocities

$R$	Radius of curvature of the road
$\theta$	Vehicle's orientation
$x''$	Curvature of x direction
$y''$	Curvature of y direction



## LIST OF ABBREVIATIONS

MIROS	Malaysian Institute of Road Safety Research
SA	Steering angle



## **CHAPTER 1**

### **INTRODUCTION**

#### **1.1 Background of the Project**

Malaysia has high rate of vehicle accidents involving some degree of driver behavior <sup>[1]</sup>. Figure 1.1 shows the road accident data in Malaysia. Number of road crashes increase every year as shown in the figure below. In the year 2013, MIROS recorded a total of 477,204 road crashes. A total of 6917 road deaths were recorded in the year 2012. The behavior of the implicated driver is usually the primary cause. This includes driver fatigue, drowsiness or lacking of response time which may lead to accidents. Therefore, in order to prevent such accidents from happening, an intelligent threat assessment analysis will be created.

A student needs to design and create an analysis for threat assessment of wheeled mobile robot. Parameters such as speed, mass of vehicle, impact force are needed to estimate the possible output. The output involve is the suitable position of host vehicle during or to avoid a collision. The simulations will be done using Matlab with different cases of possible collisions/accidents. A decision made for the vehicle to avoid collisions or accidents are based on the output obtained which is impact force and time of collision. The expected outcome of this project is to generate an analysis for threat assessment to prevent accidents by simulation.

Year	Registered Vehicles	Population	Road Crashes	Road Deaths	Serious Injury	Slight Injury	Index per 10,000 Vehicles	Index per 100,000 Population	Indeks per billion VKT
1997	8,550,469	21,665,600	215,632	6,302	14,105	36,167	7.37	29.1	33.57
1998	9,141,357	22,179,500	211,037	5,740	12,068	37,896	6.28	25.8	28.75
1999	9,929,951	22,711,900	223,166	5,794	10,366	36,777	5.83	25.5	26.79
2000	10,598,804	23,263,600	250,429	6,035	9,790	34,375	5.69	26	26.25
2001	11,302,545	23,795,300	265,175	5,849	8,680	35,944	5.17	25.1	23.93
2002	12,068,144	24,526,500	279,711	5,891	8,425	35,236	4.9	25.3	22.71
2003	12,819,248	25,048,300	298,653	6,286	9,040	37,415	4.9	25.1	22.77
2004	13,828,889	25,580,000	326,815	6,228	9,218	38,645	4.52	24.3	21.1
2005	15,026,660	26,130,000	328,264	6,200	9,395	31,417	4.18	23.7	19.58
2006	15,790,732	26,640,000	341,252	6,287	9,253	19,885	3.98	23.6	18.69
2007	16,813,943	27,170,000	363,319	6,282	9,273	18,444	3.74	23.1	17.6
2008	17,971,901	27,730,000	373,071	6,527	8,868	16,879	3.63	23.5	17.65
2009	19,016,782	28,310,000	397,330	6,745	8,849	15,823	3.55	23.8	17.27
2010	20,188,565	28,910,000	414,421	6,872	7,781	13,616	3.4	23.8	16.21
2011	21,401,269	29,000,000	449,040	6,877	6,328	12,365	3.21	23.7	14.68
2012	22,702,221	29,300,000	462,423	6,917	5,868	11,654	3.05	23.6	13.35
2013	23,819,256	29,947,600	477,204	6,915	4,597	8,388	2.9	23.1	12.19
2014	25,101,192	30,300,000	476,196	6,674	4,432	8,598	2.66	22	10.64

Figure 1.1: General Road Accident Data in Malaysia (1997 – 2014) – Malaysian Institute of Road Safety Research (MIROS) <sup>[2]</sup>

## 1.2 Problem Statement

Driver's action just before an accident is able to cause major injury or high impact force to the driver. Experienced drivers are able to make decision in a critical situation in order to avoid collision. The action during the short response time includes braking, acceleration or steering to avoid accidents. An appropriate decision making of the driver needs to be correct in order to prevent accidents from happening.

## 1.3 Project Objectives

1. To simulate the vehicle's maneuver trajectory in order to prevent accidents.
2. To estimate the possible impacts of the accidents for threat assessment analysis.
3. To provide an appropriate decision making for the driver by assessing different vehicle's maneuver conditions.

## **1.4 Project Scope**

### **1. Study of vehicle dynamics**

A good designed modeling of a system is needed in order to create an intelligent control system. Mathematical model of a vehicle is described in this thesis, which includes acceleration and braking. In addition to that, kinematic model is also described to obtain the position and coordinate of the vehicle in a certain instant.

### **2. Study of collision and impact**

Mathematical formula of collision and impact are needed to estimate the impact force of a collision. Different cases of driver's maneuver uses different mathematical formula to calculate each impact forces.

### **3. Matlab/Simulink**

Matlab is a software used for various simulations, signal processing or as a calculator. For this project, Simulink is used. It adds graphical multi-domain simulation and model-based design for dynamic and embedded systems. This is for the purpose of implementation of analysis.



## REFERENCE(S)

- [1] Kareem, A. Review of global menace of road accidents with special reference to Malaysia-a social perspective. (2003).
- [2] <https://www.miros.gov.my/1/page.php?id=17>
- [3] <http://www.physicsclassroom.com/class/newtlaws/Lesson-3/Newton-s-Second-Law>
- [4] <http://expertdirectory.arcnetwork.com/north-carolina/jamestown/news/the-physics-of-a-collision-4>
- [5] <http://hyperphysics.phy-astr.gsu.edu/hbase/carc.html#cc3>
- [6] <http://hyperphysics.phy-astr.gsu.edu/hbase/impulse.html>
- [7] <http://www.physicsclassroom.com/mmedia/momentum/trece.cfm>
- [8] <http://study.com/academy/lesson/elastic-and-inelastic-collisions-difference-and-principles.html>
- [9] <http://hyperphysics.phy-astr.gsu.edu/hbase/colsta.html#c2>
- [10] <http://hyperphysics.phy-astr.gsu.edu/hbase/inecol.html#c1>
- [11] <http://ritzel.siu.edu/courses/302s/vehicle/vehicledynamics.htm>
- [12] Hamid, U. Z. A., Zamzuri, H., Rahman, M. A. A., & Yahya, W. J. A Safe-Distance Based Threat Assessment with Geometrical Based Steering Control for Vehicle Collision Avoidance. Journal of Telecommunication, Electronic and Computer Engineering (JTEC), 8(2), 53-58. (2016).

- [13] Brannstrom, M., Coelingh, E., & Sjoberg, J. Model-based threat assessment for avoiding arbitrary vehicle collisions. *IEEE Transactions on Intelligent Transportation Systems*, 11(3), 658-669. (2010).
- [14] Gray, A., Ali, M., Gao, Y., Hedrick, J. K., & Borrelli, F. A unified approach to threat assessment and control for automotive active safety. *IEEE Transactions on Intelligent Transportation Systems*, 14(3), 1490-1499. (2013).
- [15] <http://www.edy.es/dev/docs/pacejka-94-parameters-explained-a-comprehensive-guide/>
- [16] Hosseini, S., Murgovski, N., de Campos, G. R., & Sjöberg, J. Adaptive forward collision warning algorithm for automotive applications. In *American Control Conference (ACC)*, 2016 (pp. 5982-5987). IEEE. (2016, July).
- [17] <http://hyperphysics.phy-astr.gsu.edu/hbase/crstp.html>
- [18] Wei, Y., Meng, H., Zhang, H., & Wang, X. Vehicle frontal collision warning system based on improved target tracking and threat assessment. In *Intelligent Transportation Systems Conference, 2007. ITSC 2007. IEEE* (pp. 167-172). IEEE. (2007, September).
- [19] [https://www.miros.gov.my/1/publications.php?id\\_page=19&id\\_event=374](https://www.miros.gov.my/1/publications.php?id_page=19&id_event=374)
- [20] <https://crashstats.nhtsa.dot.gov/Api/Public/ViewPublication/811059>